englisch

Declaration of performance

1309-CPR-0096

1. Door hinge model: Türband 4 AT, Türband 4, in 3 parts

2. Ident. No.: M951_, M952_, M953_, M954_, M955_, M956_, M961_,

M962_, M963_, M964_, M965_, M966_, M971_, M972_, M973_, M974_, M975_, M976_, M977_, M978_, M979_, M980_, M981_, M982_, M983_, M984_, M985_, M986_, M987_, M988_, M997_, M998_, M999_, M159_, M900B0009

A951_, A952_, A953_, A954_, A955_, A956_, A961_, A962_, A963_, A964_, A965_, A966_, A971_, A972_, A973_, A974_, A975_, A976_, A977_, A978_, A981_, A982_, A997_, A998_,

A999_, A979*_, A980*_, A159_

3. Intended use: Doors

4. Manufacturer: Dr. Hahn GmbH & Co. KG

Postfach 30 01 09 41181 Mönchengladbach

5. System for the assessment of the constancy of performance: 1

6. Harmonised standard: EN 1935:2002/AC:2003

7. Notified body: PIV, No. 1309, Prüfinstitut Schlösser und Beschläge,

Velbert (Germany) as the notified testing lab in accordance with EN 1935:2002 has performed the initial test regarding 8.1 to 8.9 and has prepared the

classification reports

8. Essential characteristics:

Essential characteristic	Performance	Harmonised technical
		specification
8.1 Usage class	4	EN 1935:2002/AC:2003
8.2 Test cycles in case of continuous	200.000	EN 1935:2002/AC:2003
operation		
8.3 Mass of the door	100/160 kg	EN 1935:2002/AC:2003
8.4 Fire resistance	0/1	EN 1634-1
8.5 Safety	1	EN 1935:2002/AC:2003
8.6 Corrosion resistance	0/4/5	EN 1670:2007
8.7 Anti-burglary resistance/protection	1	EN 1935:2002/AC:2003
8.8 Hinge class	12/14	EN 1935:2002/AC:2003
8.9 Dangerous substances	-	EN 1935:2002/AC:2003

9. The performance of the product listed under Nos. 1 and 2 corresponds to the declared performance listed under No. 8.

Signed for the manufacturer and on behalf of the manufacturer by:

Falk Füllgraf

Head of Application Engineering Mönchengladbach, 11.05.2020



PIV Prüfinstitut Schlösser und Beschläge Velbert Wallstraße 41 – D 42551 Velbert Institutsleitung: Andrea Horsthemke (B.Eng.)

Tel 0049-(0)2051-9506 5

Fax 0049-(0)2051-9506 69 Mail: info@piv-velbert.de



Zertifikat der Leistungsbeständigkeit

1309 - CPR - 0096

(Version: 05)

In Übereinstimmung mit der EU-Verordnung Nr. 305/2011 des Europäischen Parlaments und des Rates vom 9. März 2011 (Bauproduktenverordnung oder CPR) gilt dieses Zertifikat für das Bauprodukt

Türband 4 AT Türband 4

Artikelnummer: siehe Produktmatrix zum Zertifikat der Leistungsbeständigkeit Ausführung: 3-teiliges Aufschraubband

auf den Markt gebracht unter dem Namen oder der Handelsmarke von

Dr. Hahn GmbH & Co. KG Trompeterallee 162-170 D-41189 Mönchengladbach

und produziert in der Produktionsstätte

D-41189 Mönchengladbach Trompeterallee 162-170

Dieses Zertifikat bescheinigt, dass alle Bestimmungen zur Bewertung und Überprüfung der Leistungsbeständigkeit laut der Beschreibung in Anhang ZA der Norm

EN 1935:2002/AC:2003

im Rahmen des Systems 1 für die Leistung laut den Angaben in diesem Zertifikat angewendet werden, und dass

die Leistung des Bauprodukts als beständig bleibend bewertet wird.

Produkt Klassifizierungsschlüssel

4	7	5/7	0/1	1	0/4 (5*)	1	12/14
- Eignung für	die Verwendun	g an Türen in Ret	tungswegen	L			
- Pos. 4: Eigr	nung für die Ver	wendung an Feue	erschutzabschlüss	en für Bände	r der Klasse 14, Nach	weis MPA B	raunschweig
Nr.	14161/2008, g	ilt nicht für Säges	chutzbolzen A90	0B0037 und I	Prüfbericht Nr. (2201)	/918/19)-Kd	or vom
03.0	04.219 vom iBN	NB MPA Braunsch	weig		CONTRACTOR		
- Pos. 6: Kor	rosionsklasse 5	gemäß EN 1670:	2007 für Farbva	rianten Elektro	obraun Matt und RAL	9016 GL IC	9-Pulver
- Pos. 3 und	8: siehe Produk	tmatrix					

Dieses Zertifikat wurde erstmals am 11. April 2008 ausgestellt und bleibt gültig, bis entweder die harmonisierte Norm, das Bauprodukt, das System zur Bewertung und Überprüfung der Leistungsbeständigkeit oder die Produktionsbedingungen im Werk wesentlich verändert werden, oder bis das Zertifikat von der benannten Zertifizierungsstelle ausgesetzt oder zurückgenommen wird.

Stempel Zertifizierungsstelle

D-Velbert, 07. Mai 2020

Dieses Zertifikat hat insgesamt 6 Seiten und ersetzt das Zertifikat Nr. 1309-CPR-0096, Version 04 vom 20.05.2019.

Andrea Horsthemke (B.Eng.) Leiterin der Zertifizierungsstelle



PIV Prüfinstitut Schlösser und Beschläge Velbert Wallstraße 41 - D 42551 Velbert Institutsleitung: Andrea Horsthemke (B.Eng.) Tel 0049-(0)2051-9506 5

Fax 0049-(0)2051-9506 69 Mail: info@piv-velbert.de



1309

Anlage zum Zertifikat der Leistungsbeständigkeit

1309 - CPR - 0096

(Version: 05)

Wesentliche Merkmale	Abschnitte dieser Europäischen Norm	Mandatierte Stufen und/oder Klassen	Anmerkungen
Selbstschließend			Ų.
Anfangsmessungen des Reibmomentes	5.1		≤ 4 Nm (Klasse 12, 14)
Belastung-Verformung	5.2.1		
Seitliche/Vertikale Verschiebung unter Belastung	3.2.1		Seitlich < 2 mm Vertikal < 4 mm
Seitliche/Vertikale Verschiebung nach dem Entlasten			liegt innerhalb der gerasterten Fläche in Bild G.1
Überbelastung	5.2.2		bestanden
Scherfestigkeit	5.3		bestanden
Eignung für Brand- und/ oder Rauchschutztüren	5.6	keine	Klasse 0: bestanden Klasse 1: bestanden MPA-Gutachten Nr.:210005654-01 vom 26.11.2009 und Prüfbericht Nr. (2201/918/19)-Kor vom 03.04.219 vom iBMB MPA Braunschweig
Dauerfunktionstüchtigkeit		Keirie	03.04.217 Voil IBMB MI A Bradischweig
Dauerbetriebsprüfung	5.4		Klasse 7 / 200.000 Zyklen
Seitlicher/Vertikaler Verschleiß			liegt innerhalb der gerasterten Fläche in Bild G.2
Max. zulässiges Reibmoment			10400A 5070ARS 2000Y 505C 304C
- nach 20 Zyklen			≤ 4 Nm
			(Klasse 12, 14)
- nach Ende der Prüfung			≤ 4 Nm (Klasse 12, 14)
Korrosionsbeständigkeit	5.5		Klasse 0 nach EN 1670: unbeschichtet/ uneloxiert
			Klasse 4 nach EN 1670
			Klasse 5 nach EN 1670:2007/AC:2008 für Farbvarianten Elektrobraun Matt und RAL 9016 GL IG-Pulver



PIV Prüfinstitut Schlösser und Beschläge Velbert Wallstraße 41 – D 42551 Velbert Institutsleitung: Andrea Horsthemke (B.Eng.) Tel 0049-(0)2051-9506 5 Fax 0049-(0)2051-9506 69

Mail: info@piv-velbert.de



Anlage zum Zertifikat der Leistungsbeständigkeit

1309 - CPR - 0096

(Version: 05)

Wesentliche Merkmale	Abschnitte dieser Europäischen Norm	Mandatierte Stufen und/oder Klassen	Anmerkungen
Gefährliche Substanzen	ZA.1		Der Hersteller erklärt, dass das Produkt keine gefährlichen Stoffe enthält oder freisetzt, die die in den europäischen Normen und in nationalen Vorschriften festgelegten Höchstwerte überschreiten.



PIV Prüfinstitut Schlösser und Beschläge Velbert Wallstraße 41 – D 42551 Velbert

Institutsleitung: Andrea Horsthemke (B.Eng.) Tel 0049-(0)2051-9506 5 Fax 0049-(0)2051-9506 69

Mail: info@piv-velbert.de



Anlage zum Zertifikat der Leistungsbeständigkeit

1309 - CPR - 0096

(Version: 05)

Produktmatrix

Produktbezeichnung:	Türband 4 AT, 3-teilig
Frodukibezeichnung:	Türband 4, 3-teilig

Artikel-Nr.	A in mm	B in mm	C in mm	D in mm	Teiligkeit [Stk.]	EN 1935 [Klasse]
M9 51_	20	44,5	20,5	65	3	14
M9 52	36	44,5	20,5	65	3	14
M9 53	20	44,5	18,0	62,5	3	14
M9 54_	36	44,5	18,0	62,5	3	14
M9 55_	20	44,5	47,0	91,5	3	14
M9 56	36	44,5	47,0	91,5	3	14
M9 61	20	44,5	41,5	86,0	3	14
M9 62	36	44,5	41,5	86,0	3	14
M9 63	20	56,0	20,5	76,5	3	14
M9 64_	36	56,0	20,5	76,5	3	14
M9 65	20	56,0	18,0	74,0	3	14
M9 66	36	56,0	18,0	74,0	3	14
M9 71	20	56,0	47,0	103,0	3	14
M9 72	36	56,0	47,0	103,0	3	14
M9 73	20	56,0	41,5	97,5	3	14
M9 74_	36	56,0	41,5	97,5	3	14
M9 75	20	62,5	20,5	83,0	3	14
M9 76	36	62,5	20,5	83,0	3	14
M9 77_	20	62,5	41,5	104,0	3	14
M9 78_	36	62,5	41,5	104,0	3	14
M9 79_	20	62,5	47,0	109,5	3	14
M9 80_	36	62,5	47,0	109,5	3	14
M9 81_	20	62,5	18,0	80,5	3	14
M9 82_	36	62,5	18,0	80,5	3	14
M9 83_	22	44,5	0	44,5	3	14
M9 84_	36	44,5	0	44,5	3	14
M9 85_	22	56,0	0	56,0	3	14
M9 86_	36	56,0	0	56,0	3	14
M9 87	22	62,5	0	62,5	3	14



PIV Prüfinstitut Schlösser und Beschläge Velbert Wallstraße 41 – D 42551 Velbert Institutsleitung: Andrea Horsthemke (B.Eng.)

Tel 0049-(0)2051-9506 5 Fax 0049-(0)2051-9506 69 Mail: info@piv-velbert.de




1309

Anlage zum Zertifikat der Leistungsbeständigkeit


1309 - CPR - 0096

(Version: 05)

Artikel-Nr.	A in mm	B in mm	C in mm	D in mm	Teiligkeit [Stk.]	EN 1935 [Klasse]
M9 88	36	62,5	0	62,5	3	14
M9 97	20/36	62,5	20,0	Eckpfosten	3	14
M9 98	20/36	56,0	20,0	Eckpfosten	3	14
M9 99	20/36	44,5	20,0	Eckpfosten	3	14
M159_	20/23/30/33	40,0	20,0	60,0	3	14
M900B0009	optional					







M987_



PIV Prüfinstitut Schlösser und Beschläge Velbert Wallstraße 41 – D 42551 Velbert Institutsleitung: Andrea Horsthemke (B.Eng.)

Tel 0049-(0)2051-9506 5 Fax 0049-(0)2051-9506 69 Mail: info@piv-velbert.de




Anlage zum Zertifikat der Leistungsbeständigkeit


1309 - CPR - 0096

(Version: 05)

Artikel-Nr.	A in mm	B in mm	C in mm	D in mm	Teiligkeit [Stk.]	EN 1935 [Klasse]
A9 51_	20	44,5	20,5	65	3	14
A9 52_	36	44,5	20,5	65	3	14
A9 53_	20	44,5	18,0	62,5	3	14
A9 54_	36	44,5	18,0	62,5	3	14
A9 55_	20	44,5	47,0	91,5	3	14
A9 56_	36	44,5	47,0	91,5	3	14
A9 61_	20	44,5	41,5	86,0	3	14
A9 62_	36	44,5	41,5	86,0	3	14
A9 63_	20	56,0	20,5	76,5	3	14
A9 64_	36	56,0	20,5	76,5	3	14
A9 65_	20	56,0	18,0	74,0	3	14
A9 66_	36	56,0	18,0	74,0	3	14
A9 71_	20	56,0	47,0	103,0	3	14
A9 72_	36	56,0	47,0	103,0	3	14
A9 73_	20	56,0	41,5	97,5	3	14
A9 74_	36	56,0	41,5	97,5	3	14
A9 75_	20	62,5	20,5	83,0	3	14
A9 76_	36	62,5	20,5	83,0	3	14
A9 77_	20	62,5	41,5	104,0	3	14
A9 78_	36	62,5	41,5	104,0	3	14
A9 79_	20	62,5	47,0	109,5	3	12
A9 80_	36	62,5	47,0	109,5	3	12
A9 81_	20	62,5	18,0	80,5	3	14
A9 82_	36	62,5	18,0	80,5	3	14
A9 97_	20/36	62,5	20,0	Eckpfosten	3	14
A9 98_	20/36	56,0	20,0	Eckpfosten	3	14
A9 99_	20/36	44,5	20,0	Eckpfosten	3	14
A159	20/23/30	40	20	60	3	14



Ol Ontour#1 E: Skinsol O Hobbig - Ryther Ol hobbig - Frige





PIV Prüfinstitut Schlösser und Beschläge Velbert Wallstraße 41 - D42551 Velbert

Institutsleitung: Andreas Horsthemke (B.Eng.)

Tel 0049-(0)2051-9506 5 Fax 0049-(0) 2051-9506 69 Mail: info@piv-velbert.de

This document is a translation of the certificate by Dr. Hahn GmbH & Co. KG.

Certificate of constancy of performance

1309 - CPR - 0096 (version: 05)

In accordance with EU Regulation No. 305/2011 of the European Parliament and the Council dated 09.03.2011 (Construction Product Regulation - CPR), this certificate is valid for the construction product

Türband 4 AT Türband 4

Item number:

see product matrix for the attachment to the certificate of constancy of performance Construction: 3-piece screw-on hinge

brought on the market under the name or brand name of

Dr. Hahn GmbH & Co. KG **Trompeterallee 162-170** D-41189 Mönchengladbach

and produced at production site

D-41189 Mönchengladbach **Trompeterallee 162-170**

This certificate confirms that all provisions regarding the assessment and verification of the of the constancy of performance in accordance with the description in Annex ZA of the standard

EN 1935:2002/AC:2003

are applied in the context of System 1 for the performance in accordance with the specifications in this certificate, and that

the performance of this construction product has been assessed as remaining unchanged.

Product Classification key

4	7	5/7	0/1	1	0/4(5*)	1	12/14
---	---	-----	-----	---	---------	---	-------

Suited for installation on doors placed along emergency escape routes

Position 4: Suitability for utilisation on fire protection closures for class 14 hinges Certified by MPA Braunschweig No. 14161/2008, does not apply to saw-resistant bearing pin A900B0037 and test report Nr. (2201/918/19)-Kor dated 03.04.2019 from iBMB MPA Braunschweig

Position 6: Corrosion class 5 in accordance with EN 1670:2007 for colour variants Elektrobraun Matt and RAL 9016 GL IG powder

Position 3:and Position 8: c.f. product matrix

This certificate was issued for the first time on 11.04.2008 and remains valid until either the harmonised standard, the construction product, the system for the assessment and verification of the constancy of performance, or the production conditions at the factory are changed significantly, or until the certificate is suspended or withdrawn by the stated certification office.

This certificate has a total of 6 pages and replaces Certificate No.1309-CPR-0096, version 04, dated 20.05.2019



PIV Prüfinstitut Schlösser und Beschläge Velbert Wallstraße 41 – D 42551 Velbert Institutsleitung: Andreas Horsthemke (B.Eng.) Tel 0049-(0)2051-9506 5

CE

1309

Fax 0049-(0)2051-9506 69 Mail: <u>info@piv-velbert.de</u>

This document is a translation of the certificate by Dr. Hahn GmbH & Co. KG.

Attachment to the certificate of constancy of performance

1309 - CPR - 0096

(version: 05)

Essential characteristics	Sections of this European Norm	Mandated levels and/or grades	Comments
Self-locking Initial measurements of frictional torque	5.1		≤ 4Nm Category (12,14)
Stress - deformation Lateral/vertical shifting under stress	5.2.1		lateral < 2 mm vertical < 4 mm
Lateral/vertical shifting after being relieved			is located within the rasterized area in the picture G.1
Overloading	5.2.2		passed
shear strength	5.3		passed
Suitability for fire doors and/or smoke doors	5.6	none	Category 0 passed Category 1 passed MPA report No.: 210005654-01 from 26/11/2009 and test report no. (2201/918/19)-Kor dated 03.04.2019 dated iBMB MPA Braunschweig
Durable functionality Continuous service test Lateral/vertical wear	5.4		Category 7 / 200.000 Cycles is located within the rasterized area in the picture G.2
Max. permissible frictional torqueafter 20 cycles			≤ 4Nm Category (12,14)
after the end of the test			≤ 4Nm Category (12,14)
Corrosion resistance	5.5		Grade 0 in accordance with EN 1670 uncoated/non-anodised
			Category 4 in accordance with EN 1670,
			Grade 5 in accordance with EN 1670:2007 / AC:2008 For colour variants Elektrobraun Matt and RAL 9016 GL IG-Pulver

Hazardous substances	ZA.1		The manufacturer declares that the product does not contain or release hazardous substances that exceed the maximum values specified in the European Norms and in national regulations.
-------------------------	------	--	---

Englisch





Declaration of Conformity

REACH Regulation EC 1907/2006

Dear customer,

On 1 June 2007, the EC Regulation 1907/2006 to register, evaluate, authorise and restrict <u>chemical</u> <u>substances</u> (REACH) entered into force. The aim is to register and evaluate all chemicals used in the European Union.

Dr. Hahn GmbH & Co. KG manufactures door hinges and is thus a manufacturer of "products". We do not produce chemical substances ourselves, rather, we utilise them exclusively as aids in our production. Being such a "downstream user", we are not obligated to do any pre-registration ourselves; we depend, however, on our upstream suppliers' information and, in particular, registration of the chemical substances being used. The pre-registration phase, which ended on 1 December 2008, has been concluded in the meantime and so far has not resulted in any recognisable restrictions to our product and service programs.

Based on our current knowledge and the information provided by our upstream suppliers to date, the products we have so far supplied to you do not contain any substances that are included in the <u>List of Substances of Very High Concern (SVHC; of 20 June 2013)</u> as regards Annex XIV of the REACH Regulation.

This product information is based on the current state of our knowledge and experiences.

We are happy to answer any further questions you may have.

Best regards,

Dr. Hahn GmbH & Co. KG

Ulli Cremers

QMB

Mönchengladbach, den 24.06.2013